



# Caulk CX300

TILE & STONE INSTALLATION PRODUCTS

## DESCRIPTION

Siena Caulk CX300 is available in both Sanded and Non-Sanded textures and is available in all of Siena's 36 premium grout colors. Siena Calk CX300 is an exceptional siliconized acrylic latex caulk designed for the professional and homeowner alike, formulated for ease of use, durability and resists mold and mildew. Siena Caulk CX300 is flexible, lasting and gives a water tight seal that resists cracking on most building materials such as tile, stone, wood, glass and metal.

## BASIC USES

Siena Caulk CX300 can be used on most wet and dry applications to seal around sinks, tubs, showers, countertops, baseboards, windows and door frames. Also fills spaces between walls, thresholds, and joints between panels, glass block, stone, tiles and stucco. Siena Caulk CX300 is an exceptional adhesive for tile, glass, wood, metal, and is ideal for setting marble vanity tops to their bases. Not recommended for constant water exposure.

## STORAGE

1. Store containers in a cool, dry location
2. Store at a temperature between 40°F (4°C) and 90°F (32°C)
3. Do not store in direct contact with the ground and/or concrete
4. Store out of direct sunlight
5. Protect containers from weather and other damage
6. Siena Caulk CX300 should be used within one year

NOTE: Keep From Freezing

## RECOMMENDED SUBSTRATES

In general, tiles of the following materials can be used with Siena Caulk CX300: Stone, slate, granite, stone agglomerates, ceramic, quarry, paver, porcelain and clay. Caulking can also be used on glass, wood, metal, stucco and wall joints.

## SURFACE PREPARATION

All surfaces to receive application must be stable, structurally sound, dry, clean and free of debris, dirt, dust, efflorescence, grease, oils, curing agents and cleaning solutions that would hinder proper bond. For more complete installation procedures see the TCNA (Tile Council of North America) Handbook & ANSI A108.5.

## APPLICATION

Rubber gloves and proper eye wear are recommended when working with Siena Caulk CX300.

1. Use the appropriate size caulking gun.
2. Cut plastic nozzle according to the size of the joint or area of application.
3. Apply Siena Caulk CX300 into joint with uniform and smooth consistency.
4. Wipe away any excess caulk with a damp sponge immediately after application before it fully cures.
5. Dispose of empty cartridge and saturated sponges according to state and local regulations.

## MATERIAL CALCULATOR

Visit the Siena web site at [www.SienaProducts.com](http://www.SienaProducts.com) and click on the "Material Calculator" tab for recommended products and to calculate the amount of materials needed for each project. Always follow all manufacturers' recommendations and warranty information prior to any tile or stone installation.

## CURING

Cure the freshly applied material for at least 24 hrs. Curing time may vary due to porosity of substrate, ambient temperatures and humidity.

## PACKAGING

This product is packaged in a 10.5 fl.oz. (310 ml) cartridge.

## LIMITATIONS

Do not apply Siena Caulk CX300 when temperatures fall below 40°F (4°C). For interior use only. Relative humidity in excess of 90% would substantially delay curing time.

NOTE: Due to the nature of portland cement grouts and stuccos, exact color match to these products may vary. Matching color charts may also vary due to differences in manufacturing and texture.

# Caulk CX300

TILE & STONE INSTALLATION PRODUCTS

## COVERAGE

Approximately 25 linear feet (7.62 m) per cartridge for a 1/4" x 1/4" (6 x 6 mm) joint. Maximum joint width and depth should not exceed 1/4" (6 mm).

## CLEANING

Clean hands and tools with water. Clean up any misapplied sealant with a damp cloth or sponge.

## SAFETY

Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush immediately with running water for at least 15 minutes. Consult a physician immediately. Do not take internally. Be sure to provide adequate ventilation in enclosed areas. Use of an approved respirator is recommended.

## WARNING

Omega Products International, Inc., as a blender of processed material in the State of California, is required by Proposition 65 to warn that one or more of the components contained in this product, could contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. The State of California (Proposition 65) requires this warning in the absence of definitive testing to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacturing, distribution and intended use. User is solely responsible for the legal disposal of this container and/or its contents.

**KEEP OUT OF REACH OF CHILDREN**

## DISCLAIMER

Omega Products International, Inc. [Manufacturer] MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE PRODUCT SOLD HEREIN. The recommendations, suggestions, statements and technical data are based on the best knowledge available to Manufacturer and are given for informational purposes ONLY and without any responsibility for their use. It is expressly understood and agreed, as a condition of the use of this product, that the buyer's sole and exclusive remedy for any claimed defective product against Manufacturer shall be the replacement of products actually proven to be defective. Handling and use of the products are beyond the control of Manufacturer; therefore, no warranty is made, expressed or implied, as to the results obtained from the use of the product or against any claims for infringement of patents resulting from use of the product. Under no circumstance shall Manufacturer be liable for incidental or consequential damages arising out of the use or the improper application of the product. Before applying the product, the user shall determine the suitability of the product for his/her independent use, assuming all risks and liability whatsoever in connection therewith. This writing constitutes a complete and exclusive statement of the understanding between Manufacturer and Buyer.

## CLAIMS

Any Claimant shall notify Manufacturer immediately in writing of any alleged defect in the material. Claimant will provide Manufacturer with a reasonable and exclusive opportunity to investigate and test for the alleged defect. For any claim that is not valid Claimant agrees to pay Omega's reasonable charges, including travel and labor associated with investigation of such claim.

## TECHNICAL ASSISTANCE

Technical assistance and information is available by calling Omega Products International, Inc. at (800) 600-6634 or FAX (951) 520-2594 or by e-mail at "info@omega-products.com".

## WARRANTY

The following is made in lieu of all expressed and implied rights, warranties and conditions, statutory or otherwise. The Manufacturer's only obligation shall be to replace such quantity of products proven to be defective within one year following the date of manufacture, provided that the alleged defective product is returned prepaid to the Manufacturer's plant and is accompanied with proof of purchase and batch number.

Manufactured by



**The Professional's Choice**

1681 CALIFORNIA AVE., CORONA, CA 92881  
800.600.6634 • FAX: 951.520.2594 • SIENAPRODUCTS.COM