



Grout Stain ST300

GROUT STAIN



PACKAGING

8 fl.oz. (240 ml) Bottle

STORAGE

Store containers in a cool, dry location. Store at a temperature between 40°F (4°C) and 90°F (32°C). Do not store in direct contact with the ground and/or concrete. Store out of direct sunlight. Protect containers from weather and other damage. Siena Grout Stain ST300 should be used within one year

NOTE: Keep From Freezing. Dispose of empty container and sponges according to state and local regulations.

MATERIAL CALCULATOR

Visit the Siena web site at www.SienaProducts.com and click on the "Material Calculator" tab for recommended products and to calculate the amount of materials needed for each project. Always follow all manufacturers' recommendations and warranty information prior to any tile or stone installation.

Siena Grout Stain ST300 is a long lasting, waterborne urethane acrylic used to change and renew the color of sanded or non-sanded grout joints. It also seals and protects grout from moisture and staining. Siena Grout Stain ST300 is available in all of Siena's 36 premium grout colors.

FEATURES	BENEFITS
Interior & Exterior	Highly Wear Resistant
Change or Renew Color	Seals Grout Joints


BASIC USES

Siena Grout Stain ST300 can be used to change and/or renew the color of sanded or non-sanded grout joints. Siena Grout Stain ST300 also seals and protects grout from moisture and staining.

SURFACE PREPARATION

Before using Siena Grout Stain ST300 to color your grout, test first on a small inconspicuous area. Test for previously applied sealers by applying a few drops of water to grout joint. If water beads, a sealer is present and must be removed before application of this stain. Test a small area, according to application instructions, with a minimum of 2 hours cure time to ensure desired results. The stain should be easily removed from the tile but bonded permanently to the grout joint. If stain is easily removed from grout joint, allow longer curing.

NOTE: Allow at least 7 days curing time for new grout prior to applying Siena Grout Stain ST300. Existing grout must be clean, dry and free of dirt and grease. Clean grout with a neutral grout cleaner. Previously applied sealers must be removed using a sealer and adhesive remover. Porous tiles must be sealed prior to application of stain to ensure the grout stain does not penetrate into the tile.





Grout Stain ST300

GROUT STAIN

APPLICATION

1. Shake well before using
2. Do not apply when temperature is below 40°F (4°C) or above 80°F (26°C)
3. Pour a small amount into a dish or container
4. Using a bristle brush or sponge brush, dip into colorant and apply a thin coat to grout using a back and forth motion
5. Try to limit the amount of stain that gets on the tile
6. Allow a minimum of 2 hours drying time between coats
7. Allow stain to dry at least 20 minutes but not more than 30 minutes (time will vary depending on ambient temperature - test before application)
8. After grout stain has dried on the joint, dampen the area with water and let set 5 minutes before removing excess grout stain from the surface of the tile using a nylon scrub pad
9. Avoid direct scrubbing on grout joints for at least 20 days to allow stain to reach maximum durability

NOTE: If you are going from a dark to a lighter grout color, 2 or more applications of stain may be necessary.

NOTE: Use Caution when cleaning tiles that may scratch or become damaged from scrubbing. Test for potential tile damage on an inconspicuous area prior to use.

NOTE: Exact match to grout color charts may vary due to differences in manufacturing and texture.

MAINTENANCE

For routine cleaning of stained grout, use water based cleaners. Do not use solvents.

CAUTION

Some colors contain from 0.002% - 0.15% Carbon Black (CAS#1333-86-4) which has been identified by the state of California as a carcinogen. Wear rubber gloves and eye protection. Do Not Take Internally. If ingested do not induce vomiting. If contact with eyes or skin, flush with water. If irritation persists seek medical attention.

LIMITATIONS

Do not apply Siena Caulk CX300 when temperatures fall below 40°F (4°C). For interior use only. Relative humidity in excess of 90% would substantially delay curing time.

NOTE: Due to the nature of portland cement grouts and stuccos, exact color match to these products may vary. Matching color charts may also vary due to differences in manufacturing and texture.

COVERAGE

Per 8 fl. oz. (240 ml)	
4" x 4" tile x 1/4" joint	80 ft ²
6" x 6" tile x 1/4" joint	90 ft ²
12" x 12" tile x 1/4" joint	125 ft ²

NOTE: Coverage will vary depending on width and porosity of grout joint, size of tile and method of application. For additional grout coverage information, please refer to the Siena web site at www.SienaProducts.com and click on "Materials Calculator."

TECHNICAL ASSISTANCE

Technical information is available on our web site at: SienaProducts.com, by calling Omega Products International at: 800.600.6634, or by email at: info@omega-products.com

CLEANING

Clean hands and tools with water. Clean up any misapplied sealant with a damp cloth or sponge.

WARNING

Omega Products International, as a blender of processed material in the State of California, is required by Proposition 65 to warn that one or more of the components contained in this product, could contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. The State of California (Proposition 65) requires this warning in the absence of definitive testing to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacturing, distribution and intended use. User is solely responsible for the legal disposal of this container and its contents.

KEEP OUT OF REACH OF CHILDREN

Disclaimer

Omega Products International [Manufacturer] MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE PRODUCT SOLD HEREIN. The recommendations, suggestions, statements and technical data are based on the best knowledge available to Manufacturer and are given for informational purposes ONLY and without any responsibility for their use. It is expressly understood and agreed, as a condition of the use of this product, that the buyer's sole and exclusive remedy for any claimed defective product against Manufacturer shall be the replacement of products actually proven to be defective. Handling and use of the products are beyond the

control of Manufacturer; therefore, no warranty is made, expressed or implied, as to the results obtained from the use of the product or against any claims for infringement of patents resulting from use of the product. Under no circumstance shall Manufacturer be liable for incidental or consequential damages arising out of the use or the improper application of the product. Before applying the product, the user shall determine the suitability of the product for his or her independent use, assuming all risks and liability whatsoever in connection therewith. This writing constitutes a complete and exclusive statement of the understanding between Manufacturer and Buyer.