

DEMAND THE BEST IN TILE & STONE INSTALLATION PRODUCTS



BUYER'S GUIDE THE COMPLETE LINE OF SIENA PRODUCTS



TO OUR VALUED CUSTOMERS







Siena Tile and Stone Installation Products prides itself on being a leader in the commercial and residential construction markets. Siena features a full line of thin and medium set specialty mortars, waterproofing and anti-fracture membranes, self-leveling, deck mud and wall float, masonry mortars, grouts, caulking, sealers and admixtures. Our state of the art manufacturing facilities, unsurpassed quality control, and our commitment to customer service has made us the professional's choice for over 40 years.


Siena is committed to our customers' satisfaction, offering the best in both products and service. We are proud of our role as a leader in the development of new and innovative products for the tile and stone installation industry. Our comprehensive product line makes Siena a complete, seamless solution for your tile and stone installation projects. Our broad range of 36 standard grout colors, plus custom color matching, gives your customers the choices they need to insure a perfect color match.

A division of Omega Products International, Siena's high quality line of products are backed by the most complete line of exterior stucco wall systems and decorative finishes in the construction market today.

This Buyer's Guide is intended to give you the product data you need to ensure you are delivering the right products to your customers at competitive industry prices. Please visit our website for additional product information, SDS, photo gallery, technical data, material calculator, and be sure you are listed on our distributor locator at SienaProducts.com.

LIMITED 10 YEAR WARRANTY

Siena Tile & Stone Installation Products [Siena], a division of Omega Products International. [Omega] warrants that the products listed below are free from manufacturing defects under normal usage and conditions for a period of ten (10) years from the date of purchase when installed in accordance with product specifications, current TCNA (Tile Council of North America) guidelines and practices on properly prepared substrates. It is the responsibility of the owner and/or contractor to obtain and understand Omega and Siena's literature, specifications and appropriate published reports such as, but not limited to the current TCNA handbook, product data sheets, technical bulletins, etc. In order for this warranty to apply, the installation must be performed with one or more of the products listed below, and based on the appropriate product(s) being installed on a properly prepared substrate. Omega is not responsible for workmanship that is not in accordance with the product specifications, product data sheet instructions, TCNA guidelines and practices, and/or improperly prepared substrates. Structural movement, cracking, excessive deflection, lippage, warping, curling or defective tiles, improperly placed or lack of proper movement or control joints, flooding and/or water damage, acts of God or any failures to the substrate are not covered under this warranty. Shading and Efflorescence are inherent in all cement based products and are not considered a manufactures defect. Omega will not be responsible for failures when the use of non-specified products, competitor, or any product is used to alter the original formulation of the products that is not in accordance with specifications on the product's data sheet, and such uses and/or alterations will void this and all Omega and Siena warranties. This warranty is not transferable beyond the original owner





Siena Multi Purpose M100	2
Siena Multi Plus Pro M200	2
Siena Pro Set Flex M300	2
Siena Glass Tile Pro M375	2
Siena Medium M225	3
Siena Medium Set Pro M400	3
Siena Crete Admix AX400 & Siena Crete Powder	3
Siena Elasto Pro EP200	3
Siena Dragon Skin Waterproof & Anti-Fracture Membrane	4
Siena Fracture Shield Water Resistant & Anti-Fracture Membrane	4
Siena Deck Mud	4
Siena Wall Float	4
Siena Self-Leveling Underlayment (SLU)	5
Siena Self-Leveling Underlayment (SL20).	5
Siena Self-Leveling Primer	5
Siena Floor Patch SP820	5
Slena Presto Pak	6
Siena Admix AX100 Admixture	6
Siena Admix AX300 Admixture	6
Siena Mastic 625	6
Siena Premium Set 550	
Siena ThinSet 510	
Siena Fast Set 595	
Siena Fast Set Pro M75	7
Siena Sanded Grout GS300	
Siena Non-Sanded Grout NS200	
Siena Epoxy Grout & Mortar	8
o:	_
Siena Caulk CX300 - Sanded or Smooth.	
Siena Grout Stain ST300	9
Siena Type S Mortar	10
Siena Stone Veneer Mortar (SVM)	
Siena Premium Stone Veneer Mortar Polymer-Modified (PSVM)	
Siena Masonry & Surface Sealer	
Sieria Piasoni y & Surrace Sealer	. IU



POLYMER-MODIFIED THIN SET MORTARS



SIENA MULTI PURPOSE M100

An economic polymer-modified mortar manufactured with portland cement to produce a high quality mortar with good bond strength, open time and coverage. Siena Multi Purpose M100 is used in a wide variety of installs over cured cement and concrete slabs, masonry, brick, backer board, and properly prepared ceramic tile. Used in interior and exterior applications of most tiles and stones, and can be used on floors, walls and in mortar beds up to 3/16" for residential and light commercial projects. Available in white and grey, and complies with the requirements of ANSI A118.4 and A118.11.

Coverage

Notch Trowel - Coverage May Vary. 1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) - 95 ft² (8.8 m²) 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) - 75 ft² (7.0 m²) 1/2" x 1/2" x 1/2" (13 x 13 x 13 mm) - 55 ft² (5.1 m²)

Packaging

50 lb (22.7 kg) bags

Pallet Quantities

56 bags per pallet - 2,800 lbs (1,271 kg) net

SKU	COLOR
X130-0450	Grey
X130-0550	White



SIENA MULTI PLUS PRO M200

A premium multi-purpose polymer-modified mortar manufactured with portland cement to produce a high quality mortar with exceptional bond strength, great open time and coverage, and is used to install porcelain and other types of high dense, non porous tiles and stones. Siena Multi Plus Pro M200 is used in a wide variety of installs over cured cement and concrete slabs, masonry, brick, backer board, properly prepared ceramic tile. Siena Multi Plus Pro M200 is used in interior and exterior applications of most tiles and stones, and can be used on floors, walls and in mortar beds up to 3/16" for residential and commercial projects, and can be used over Exterior Grade Plywood (EGP). Siena Multi Plus Pro M200 is available in white and grey, and complies with the requirements of ANSI A118.4 and A118.11.

Coverage

Notch Trowel - Coverage May Vary. 1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) - 95 ft² (8.8 m²) 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) - 75 ft² (7.0 m²) 1/2" x 1/2" x 1/2" (13 x 13 x 13 mm) - 55 ft² (5.1 m²)

Packaging

50 lb (22.7 kg) bags

Pallet Quantities

56 bags per pallet - 2,800 lbs (1,271 kg) net

SKU	COLOR
X130-0650	Grey
X130-0750	



SIENA PRO SET FLEX M300

A premium flexible polymer-modified mortar manufactured with portland cement to produce a high quality mortar with exceptional bond strength, higher flexibility, greater open time and coverage, and is used to install porcelain and other types of high dense, non porous tiles and stones. Used as a flexible mortar for interior and exterior applications of most tiles and stones. Can be used on floors, walls and in mortar beds up to 3/16" in residential and commercial projects. Siena Pro Set Flex M300 will span cracks up to 1/16" (1.6 mm) in substrates with limited vibration and deflection, and can be used over exterior grade plywood (EGP). Available in white or grey, and complies with the requirements of ANSI A118.15

Coverage

Notch Trowel – Coverage May Vary. 1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) - 95 ft² (8.8 m²) 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) - 75 ft² (7.0 m²) 1/2" x 1/2" x 1/2" (13 x 13 x 13 mm) - 55 ft² (5.1 m²)

Packaging

50 lb (22.7 kg) bags

Pallet Quantities

56 bags per pallet - 2,800 lbs (1,271 kg) net

SKU	COLOR
X130-0850	Grey
X130-0950	$\ldots \ldots White$



SIENA GLASS TILE PRO M375

A high performance, premium flexible polymer-modified mortar designed to give superior bond strength to the most demanding tile and stone installations. Siena Glass Tile Pro M375 is manufactured with portland cement and proprietary additives to produce a flexible, high quality tile and stone adhesive, with non-sagging and mildew resistant properties. Siena Glass Tile Pro M375 has exceptional strength, adhesion, open time and coverage beyond other premium mortars. Siena Glass Tile Pro M375 is used in interior and exterior application of most tiles, stones, decorative glass or metal tiles, pavers, brick, thin brick, and stone veneers. Siena Glass Tile Pro M375 can be used on floors, walls and in mortar beds up to 3/16" in residential and commercial projects. It is available in gray, and in a consistent white color for translucent tiles, and will span cracks up to 1/8". Siena Glass Tile Pro M375 exceeds the requirements of ANSI A118.15

Coverage

Notch Trowel - Coverage May Vary. 1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) - 48 ft² (8.8 m²) 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) - 38 ft² (7.0 m²) 1/2" x 1/2" x 1/2" (13 x 13 x 13 mm) - 28 ft² (5.1 m²)

Packaging

25 lb (11.36 kg) bags

Pallet Quantities

100 bags per pallet - 2,500 lbs (1,136 kg) net

SKU	COLOR
X130-2650	Grey
X130-2750	White

LFT • LHT • SPECIALTY MORTARS





SIENA LFT, LHT M225

A polymer-modified medium bed mortar manufactured with portland cement to produce a high quality mortar with increased bond strength, easy adjustability, reduced lippage, greater open time and coverage than standard medium bed mortars. Siena LFT, LHT M225 is specially formulated for the installation of most large format and un-gauged tiles and stones without the need of leveling the receiving substrate. Siena LFT LHT M225 can be used for interior and exterior application and on floors in residential and commercial projects. Siena LFT, LHT M225 can be use as a setting bed 3/16" up to 3/4" thick. For large format and un-gauged tiles and stone in vertical installs, use Siena LFT, LHT Pro M400 which contains non-slip/ non-sag chemicals to help eliminate sliding. Siena LFT, LHT M225 is available in white or gray, and complies with the requirements of ANSI A118.4 and A118.11.

Coverage

Notch Trowel - Coverage May Vary. 1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) - 95 ft² (8.8 m²) 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) - 75 ft² (7.0 m²) 1/2" x 1/2" x 1/2" (13 x 13 x 13 mm) - 55 ft² (5.1 m²) Packaging

50 lb (22.7 kg) bags

Pallet Quantities

56 bags per pallet - 2,800 lbs (1,271 kg) net

SKU	COLOR
X130-4021	Grey
X130-4020	White

SIENA LFT, LHT PRO M400

A premium polymer-modified medium bed mortar manufactured with portland cement and proprietary additives to produce a high quality non-sag / non-slip mortar with increased bond strength, easy adjustability, reduced lippage, greater open time and coverage than standard medium bed mortars. Siena LFT, LHT Pro M400 is specially formulated with non-sag / non-slip properties for the installation of most large format and un-gauged tiles and stones without the need of leveling the receiving substrate. Siena LFT, LHT Pro M400 can be used for interior and exterior applications and on floors or walls in residential and commercial projects. On floors it can be used as a setting bed 3/16" up to 3/4" thick. Siena LFT, LHT Pro M400 is available in white or grey, and complies with the requirements of ANSI A118.4 and A118.11.

Coverage

Notch Trowel - Coverage May Vary. 1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) - 95 ft² (8.8 m²) 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) - 75 ft² (7.0 m²) 1/2" x 1/2" x 1/2" (13 x 13 x 13 mm) - 55 ft² (5.1 m²)

Packaging

50 lb (22.7 kg) bags

Pallet Quantities

56 bags per pallet - 2,800 lbs (1,271 kg) net

SKU	COLOR
X130-1050	 Grey
X130-1150	 White

SIENA CRETE ADMIX AX400 & SIENA CRETE POWDER

A premium admixture designed to be used with Siena Crete Powder or a site mixture of sand and cement to create a premium polymer-modified mortar, which offers higher bond strength, greater flexibility, resistance to frost, longer open time and better coverage than standard mortars. Siena Crete Admix AX400 is used in demanding applications of tile, stone, brick, and thin brick installs, high moisture environments, and heavy traffic areas. The increased flexibility allows for substrate adjustments from climate and temperature changes without shearing. Siena Crete Admix AX400 can be used on floors, walls and in mortar beds as thin as 3/32" in interior and exterior, residential and commercial projects. Siena Crete Powder is available in white or grey, and complies with the requirements of ANSI A118.15 (when mixed with Siena Crete Powder) certified by H.C. Muddox Interstate Brick.

Coverage

Notch Trowel - Coverage May Vary. 1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) - 95 ft² (8.8 m²) 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) - 75 ft² (7.0 m²) 1/2" x 1/2" x 1/2" (13 x 13 x 13 mm) - 55 ft² (5.1 m²)

Packaging

AX400 - 5 gal (18.9 L) pails, 55 gal (208.2 L) drum Siena Crete Powder - 50 lb (22.7 kg) bag

Pallet Quantities

32 - 5 gal. pails per pallet, 2,080 lbs (942 kg) net 56 bags per pallet - 2,800 lbs (1,271 kg) net

SIZE
5 gal.
55 gal.
COLOR
Grey
White



SIENA ELASTO PRO EP200

An exceptional elastomeric modified mortar and anti-fracture membrane manufactured with acrylic polymers and portland cement to produce a high quality flexible mortar with unmatched strength and flexibility. Siena Elasto Pro EP200 is specially formulated for the installation of most tiles and stones over substrates susceptible to deflections up to 1/240 of span. As an anti-fracture membrane, it can isolate preexisting and stress cracks, and prevent them from transferring through to the finished goods. Siena Elasto Pro EP200 can be used in interior and exterior applications, on floors or walls in residential and commercial projects. Siena Elasto Pro EP200 is available in white or grey, and is a two part product (Elasto Mix AX200 & Elasto Pro EP200 Powder). Exceeds ANSI A108.5, ANSI A118.12.

Coverages

Notch Trowel – Coverage May Vary. $1/4" \times 1/4" \times 1/4" (6 \times 6 \times 6 \text{ mm})$ - 75 ft² (7.0 m²) $1/4" \times 3/8" \times 1/4" (6 \times 9.5 \times 6 \text{ mm})$ - 55 ft² (5.1 m²) $1/2" \times 1/2" \times 1/2" (13 \times 13 \times 13 \text{ mm})$ - 45 ft² (4.2 m²) Membrane Coverage May Vary.

Thickness at 1/16" (1.6 mm) - 95 ft² (8.8 m²)

Packaging

25 lb (11.35 kg) bags, 2 gallon (7.56 L) jugs

Pallet Quantities

64 - 2 gal. jugs per pallet, 1,100 lbs (498 kg) net 100 bags per pallet - 2,500 lbs (1,135 kg) net

SKU	COLOR
X130-1750	Grey
X130-1850	White







MEMBRANES • SURFACE PREP

SIENA DRAGON SKIN

WATERPROOF & ANTI-FRACTURE MEMBRANE

A premium ready to use, and IAPMO certified water-proofing and anti-fracture membrane, manufactured with latex polymers to produce a high quality elastomeric, and fast drying barrier. It's easily applied using a trowel, roller, paint brush or sprayer, and is available in both purple and white colors. Dragon Skin is used on recommended substrates as a barrier to water migration for load bearing tile and stone installations, and as an anti-fracture membrane used to prevent shrinkage or non-structural cracks up to 1/8" transmitting from the substrate through to the finished goods. Use polymer modified mortars meeting ANSI A118.4 or A118.11 for tile or stone installations over the Siena Dragon Skin membrane. Dragon Skin bonds to most surfaces, dries quickly (less than two hours), low VOC - has almost no odor, is not sticky or messy, and is ready to flood test in as little as 24 hours. Exceeds the requirements for ANSI A118.10 for waterproofing membranes, and ANSI A118.12 for anti-fracture membranes. It can be used in residential, commercial, interior and exterior tile and stone installations. IAPMO has listed Siena Dragon Skin for use as a shower pan liner (IAPMO R&T File # 6892).

Coverage - Coverage May Vary.

(1 coat) 30 mil wet thickness: 100 ft² (9.3 m²) per gal. (2 coat) 60 mil wet thickness: 50 ft² (4.6 m²) per gal. Note: Waterproofing membrane must be two coats.

Packaging

1 gal. (3.8 L) jugs, 3.5 gal. (13.3 L) pails 5 gal. (18.9 L) pails.

Pallet Quantities

128 – 1 gal. jugs per pallet, 1,075 lbs (487 kg) net 48 – 3.5 gal. pails per pallet, 1,411 lbs (639 kg) net 32 – 5 gal. pails per pallet, 1,344 lbs (609 kg) net

SKU	SIZE
X130-4007	. 1 gal.
X130-4008	3.5 gal.
X130-4009	. 5 gal.



SIENA FRACTURE SHIELD

WATER RESISTANT & ANTI-FRACTURE MEMBRANE

A ready to use anti-fracture, crack isolation and water resistant membrane, manufactured with latex polymers to produce a high quality elastomeric barrier that protects tile and stone floors from cracks due to minor surface movement. Siena Fracture Shield is used on recommended substrates to prevent shrinkage or non-structural cracks up to 1/8" from transmitting from the substrate through the finished goods. Use polymer modified mortars meeting ANSI A118.4 or A118.11 for tile or stone installations over the Siena Fracture Shield membrane. Fracture Shield is easily applied with a trowel, roller or brush. Fracture Shield can be used in residential, commercial, interior and exterior tile and stone applications, and exceeds the crack isolation requirements of ANSI A118.12

Coverage — Coverage May Vary.

(1 coat) 30 mil wet thickness: 100 ft² (9.3 m²) per gal. (2 coat) 60 mil wet thickness: 50 ft² (4.6 m²) per gal.

Packaging

1 gal. (3.8 L) jugs, 3.5 gal. (13.3 L) pails, 5 gal. (18.9 L) pails. **Pallet Quantities**

128 – 1 gal. jugs per pallet, 1,075 lbs (487 kg) net 48 – 3.5 gal. pails per pallet, 1,411 lbs (639 kg) net 32 – 5 gal. pails per pallet, 1,344 lbs (609 kg) net

SKU	SIZE
X130-4011	1 gal.
X130-4012	3.5 gal.
X130-4013	5 gal.



SIENA DECK MUD

A deck mud that is used to create a high strength cementitious substrate and setting bed for horizontal applications of most tile or stone installations. Designed for most interior and exterior, commercial and residential applications such as floors, shower pans, countertops, depressed slabs, and plywood substrates where a waterproof membrane is used. Siena Deck Mud is a factory blended mortar consisting of portland cement which complies with ASTM C150 and graded sand which complies with ASTM C144.

Coverage — Coverage May Vary.

50 lb. bag: 1" (6.1 ft²), 1-1/2" (4.0ft²), 2" (3.0 ft²) 75 lb. bag: 1" (9.2 ft²), 1-1/2" (6.1ft²), 2" (4.5 ft²)

Packaging

50 lb (22.7 kg) bags and 75 lb (34 kg) bags.

Pallet Quantities

56 - 50 lb. bags per pallet, 2,800 lbs (1,271 kg) net 42 - 75 lb. bags per pallet, 3,750 lbs (1,700 kg) net

SKU	SIZE
X130-4000	50 lb.
X130-4001	



SIENA WALL FLOAT

A wall float designed to be used as a scratch and brown coat over open framing with metal lath to create a solid vertical substrate used for most tile and stone installations. Siena Wall Float may be used for interior and exterior, residential and commercial applications on walls and ceilings. When Siena Admix AX300 or AX400 are used in lieu of water with the Siena Wall Float, flexibility, adhesion, and water resistance are improved. Siena Wall Float is available in grey and is a mortar that consists of portland cement complying with ASTM C150, hydrated lime complying with ASTM C207, and sand complying with ASTM C144.

Coverage — Coverage May Vary.

50 lb. bag: 3/8" (16 ft²), 3/4" (8 ft²) 75 lb. bag: 3/8" (25 ft²), 3/4" (12.5 ft²)

Packaging

50 lb (22.7 kg) bags and 75 lb (34 kg) bags.

Pallet Quantities

56 - 50 lb bags per pallet, 2,800 lbs (1,271 kg) net 42 - 75 lb bags per pallet, 3,750 lbs (1,700 kg) net

SKU	SIZE
X130-4002	50 lb.
X130-4003	75 lb.

SELF LEVELING • PATCH

SIENA SELF-LEVELING UNDERLAYMENT (SLU)

A rapid setting portland cement-based mortar designed to create a smooth, level surface prior to the application of a variety of flooring such as tile, stone, carpeting, marble, resilient floor, wood, parquet and other approved floor coverings. It is designed for fast leveling of floors from 0 - 3/4" with minimum time and labor. Surfaces can be walked on in 2 to 4 hours and the floor coverings can be installed within 12 to 24 hours. It can be used over concrete, plywood, terrazzo, quarry and tile in commercial and residential projects. Siena Self-Leveling Primer must be applied prior to installing the Siena Self-Leveling products.

Coverage - Coverage May Vary. Thickness 1/8" - 60 ft² (5.7 m²) Thickness 1/4" - 30 ft² (2.86 m²) **Packaging**

50 lb (22.7 kg) bags

Pallet Quantities

56 bags per pallet - 2,800 lbs (1,271 kg) net

SKU	COLOR
X130-4004	Grey





SIENA SELF-LEVELING UNDERLAYMENT (SL20)

A rapid setting portland cement-based mortar designed to create a smooth, level surface prior to the application of a variety of flooring such as tile, stone, carpeting, marble, resilient floor, wood, parquet and other approved floor coverings. It is designed for fast leveling of floors from 1/2" – $1 \frac{1}{2}$ " with minimum time and labor. Surfaces can be walked on in 2 to 4 hours and the floor coverings can be installed within 12 to 24 hours. It can be used over concrete, plywood, terrazzo, guarry and tile in commercial and residential projects. Siena Self-Leveling Primer must be applied prior to installing the Siena Self-Leveling products.

Coverage — Coverage May Vary. Thickness 1/2" - 15 ft² (1.4 m²) Thickness 1-1/2" - 5 ft² (0.5 m²)

Packaging

50 lb (22.7 kg) bags

Pallet Quantities

56 bags per pallet - 2,800 lbs (1,271 kg) net

SKU	COLOR
X130-4010	Grey



SIENA SELF-LEVELING PRIMER

A latex based primer for use with Siena Self-Leveling Underlayment products. It is solvent free and improves the underlayment's bond over porous substrates. This is a white liquid that dries clear. It is required that Siena Self-Leveling Primer be used in all self-leveling install projects. Specially formulated to promote the adhesion of Siena Self-Leveling Underlayment products to a variety of surfaces such as concrete, plywood, stone, tile, terrazzo, cement backer boards, pavers, brick, and other approved porous substrates.

Coverage - Coverage May Vary. 300 sq. ft. (28 m²) per gal. (3.8 L)

Packaging

1 gallon (3.8 L) jugs - 4 per case 5 gallon (18.9 L) pails.

Pallet Quantities

128 - 1 gal. jugs per pallet, 1,075 lbs (487 kg) net 32 - 5 gal. pails per pallet, 1,344 lbs (609 kg) net

SKU	SIZE
X130-4006	. 1 gal.
X130-4005	. 5 gal.



SIENA FLOOR PATCH SP820

A premium, fast setting, polymer-modified cementitious patching, skim coating, ramping, leveling and finishing material. It is designed to create a smooth finish from feather edge to 1" in a single application on horizontal interior substrates. It can be used to prepare surfaces for the installation of many types of flooring, such as: carpet, wood, tile, laminate, LVT, VCT and engineered flooring. Flooring may be installed within one hour of application. Siena Floor Patch SP820 is an excellent choice to cover nonstructural imperfections in concrete surfaces to produce a clean, uniform, smooth finish

Coverage — Coverage May Vary 20 lb. bag: Approximately 50 sq ft (4.6 m²) at a 1/8" coat.

Packaging

20 lb. (9.07 kg) Bag

Pallet Quantities

20 lb. (9.07 kg) Bag -100 Bags per Pallet

SKU	COLOR
X136-4024	Grey





ACCELERATOR • ADMIX • MASTIC



SIENA PRESTO PAK

Siena Presto is a powder accelerating admixture made to use with cement-based products. Presto is a non-corrosive, non-chloride additive designed to accelerate setting times of both modified and non-modified portland cement-based products, such as tile mortars, stone veneer mortars and grouts. Siena Presto is designed to significantly reduce project timeline by accelerating setting times of portland cement-based tile mortars, stone veneer mortars and grouts. Add the desired quantity of Presto (one or two bags) to the amount of water specified in the instructions for the mortar or grout needing acceleration. Add the dry mortar or grout to the water and Presto solution according to mixing instructions for the mortar or grout product being used.

Coverage - Coverage May Vary

See coverage of mortar, grout or base product being mixed into

Packaging and Case Quantity

1 lb. (.45 kg) Bag

SKU	COLOR
X136-4023	 White



SIENA ADMIX AX100 ADMIXTURE

An acrylic admixture manufactured with high quality polymers to produce a light-duty admixture for Siena Grouts and dryset mortars. Siena Admix AX100 promotes increased flexibility, adhesion, surface appearance, and bond strength when used with Siena grouts and mortars. Siena Admix AX100 can be used to enhance the performance, density, flexibility and adhesion of non-modified mortars, such as Siena ThinSet 510, Premium Set 550, Siena Type S and Siena Stone Veneer Mortars (SVM). Siena Admix AX100 complies with ANSI A118.4 and A118.6.

Packaging

1 gallon (3.8 L) jugs - 4 per case 5 gallon (18.9 L) pails.

Pallet Quantities

128 – 1 gal. jugs per pallet, 1,088 lbs (493 kg) net 32 – 5 gal. pails per pallet, 1,360 lbs (616 kg) net

SKU	SIZE
X130-0307	1 gal.
X130-0309	5 gal.



SIENA ADMIX AX300 ADMIXTURE

Use with non-modified grouts or mortars only.

A premium acrylic admixture manufactured with high quality polymers to produce a high strength admixture for Siena dry-set mortars and masonry mortars. Siena Admix AX300 promotes increased flexibility, adhesion, surface appearance, and bond strength when used with Siena mortars. Siena Admix AX300 can be used to enhance the performance, density, flexibility and adhesion of non-modified mortars, such as Siena ThinSet 510, Premium Set 550, Siena Type S and Siena Stone Veneer Mortar (SVM). Siena Admix AX300 complies with ANSI A118.4 and A118.6. Use with non-modified grouts or mortars only.

Packaging

1 gal. (3.8 L) jugs, 4 per case 2.5 gal. (7.6 L) pails, 2 per case 5 gal. (18.9 L) pails.

Pallet Quantities

128 – 1 gal. jugs per pallet, 1,088 lbs (493 kg) net 64 – 2.5 gal. pails per pallet, 1,363 lbs (618 kg) net 32 – 5 gal. pails per pallet, 1,366 lbs (619 kg) net

SKU	SIZE
X130-0301	 1 gal.
X130-0302	 2.5 gal.
X130-0303	 5 gal.



SIENA MASTIC 625

A non-slip high performance, smooth spreading premium mastic formulated for interior installation of all types of wall and floor tiles on vertical or horizontal surfaces. Siena Mastic 625 is a Type 1 organic mastic adhesive used to install most tiles and stones. Organic mastics are not recommended for exterior use. Siena Mastic 625 can be used to install ceramic tile, mosaics tiles, glazed wall tile, quarry tile, slate and pavers, up to 12" x 12". Siena Mastic 625 is non-flammable, freeze-thaw stable to 10° F and exceeds ANSI-A-136.1.

Coverage

Notch Trowel - Coverage May Vary.

1/8" x 1/8" x 1/8" (3.2 x 3.2 x 3.2 mm) - 80 ft² (2.0 m²) 1/4" x 1/4" x 1/4" (6.4 x 6.4 x 6.4 mm) - 30 ft² (1.0 m²) 1/4" x 1/4" x 3/8" (6.4 x 6.4 x 9.5 mm) - 40 ft² (1.0 m²) 3/16" x 5/32" (4.8 x 4.8 x 4.0 mm) - 60 ft² (2.0 m²)

Packaging

1 gal. (3.78 L) jugs, 3.5 gal. (13.25 L) pails

Pallet Quantities

128 - 1 gal. jugs per pallet, 1,075 lbs (487 kg) net 48 - 3.5 gal. pails per pallet, 1,411 lbs (639 kg) net

SKU	COLOR
X130-1450	 1 gal.
X130-1550	 .3.5 gal.

NON-MODIFIED THIN SET MORTARS • FAST SET



SIENA PREMIUM SET 550

A premium mortar use with Schluter™ Ditra Systems™ and used to install tiles and stones. Siena Premium Set 550 is a dry-set mortar manufactured with portland cement, to produce a high quality non-modified mortar with high bond strength and great coverage. Siena Premium Set 550 is used in interior and exterior applications of most tiles and stones. Siena Premium Set 550 can be used on floors, walls and in mortar beds up to 3/16" in residential and commercial projects. Siena Premium Set 550 is available in either white or grey, and complies with the requirements of ANSI A118.1. If used in conjunction with Siena Acrylic Admix AX100 or AX300, it will also comply with the requirements of ANSI A118.4 and ANSI A118.11.

Coverage

Notch Trowel - Coverage May Vary. 1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) - 95 ft² (8.8 m²) 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) - 75 ft² (7.0 m²) 1/2" x 1/2" x 1/2" (13 x 13 x 13 mm) - 55 ft² (5.1 m²)

Packaging

50 lb (22.7 kg) bags

Pallet Quantities

56 bags per pallet - 2,800 lbs (1,271 kg) net

SKU	COLOR
X130-0250	Grey
X130-0350	



SIENA THINSET 510

An economical mortar used to install basic ceramic and porous tiles and stones. Siena ThinSet 510 is a dry-set mortar manufactured with portland cement, to produce a high quality non-modified mortar with good bond strength and coverage. Siena ThinSet 510 is used in interior and exterior applications of porous tiles and stones. Siena ThinSet 510 can be used on floors, walls and in mortar beds up to 3/16" in residential and light commercial projects. Siena ThinSet 510 is available in either white or grey, and complies with the requirements of ANSI A118.1. If used in conjunction with Siena Acrylic Admix AX100 or AX300, it will also comply with the requirements of ANSI A118.4 and ANSI A118.11.

Coverage

Notch Trowel - Coverage May Vary. 1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) - 95 ft² (8.8 m²) 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) - 75 ft² (7.0 m²) 1/2" x 1/2" x 1/2" (13 x 13 x 13 mm) - 55 ft² (5.1 m²)

Packaging

50 lb (22.7 kg) bags

Pallet Quantities

56 bags per pallet - 2,800 lbs (1,271 kg) net

SKU	COLOR
X130-0050	Grey
X130-0150	White



SIENA FAST SET 595

A fast setting dry-set mortar manufactured with portland cement to produce a high quality non-modified mortar. Siena Fast Set 595 enables the install and grouting to be done within two hours, and is ready for foot traffic in four hours, and is used whenever a job must be done in one day or less. Siena Fast Set 595 is available in either white or gray, and complies with the requirements of ANSI A118.1. Siena Fast Set 595 is used for interior and exterior application of porous tiles and stones. Siena Fast Set 595 can be used on floors, walls and in mortar beds up to 3/16" in residential and light commercial projects. If modified fast set mortar is needed use Siena Fast Set Pro M75.

Coverage

Notch Trowel - Coverage May Vary. 1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) - 45 ft² (4.2 m²) 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) - 35 ft² (3.3 m²) 1/2" x 1/2" x 1/2" (13 x 13 x 13 mm) - 25 ft² (2.3 m²)

Packaging

25 lb (11.35 kg) bags

Pallet Quantities

100 bags per pallet - 2,500 lbs (1,135 kg) net

SKU	COLOR
X130-2225	 Grey
X130-2235	 White



SIENA FAST SET PRO M75 (POLY-MODIFIED)

A fast setting dry-set mortar manufactured with portland cement to produce a high quality modified mortar. Siena Fast Set Pro M75 enables the install and grouting to be done within two hours, and is ready for foot traffic in four hours, and is used whenever a job must be done in one day or less. Available in either white or gray, and complies with the requirements of ANSI A118.1. Used for interior and exterior application of most tiles and stones. Siena Fast Set Pro M75 can be used on floors, walls and in mortar beds up to 3/16" in residential and commercial projects. If non-modified fast set mortar is needed use Siena Fast Set 595.

Coverage

Notch Trowel – Coverage May Vary. $1/4" \times 1/4" \times 1/4" (6 \times 6 \times 6 \text{ mm}) - 45 \text{ ft}^2 (4.2 \text{ m}^2) \\ 1/4" \times 3/8" \times 1/4" (6 \times 9.5 \times 6 \text{ mm}) - 35 \text{ ft}^2 (3.3 \text{ m}^2) \\ 1/2" \times 1/2" \times 1/2" (13 \times 13 \times 13 \text{ mm}) - 25 \text{ ft}^2 (2.3 \text{ m}^2)$

Packaging

25 lb (11.35 kg) bags

Pallet Quantities

100 bags per pallet – 2,500 lbs (1,135 kg) net

SKU	COLOR
X130-2325	 Grey
X130-2335	 White





GROUTS



SIENA SANDED GROUT GS300

A polymer-enhanced premium grout manufactured with portland cement to produce a high quality grout that requires only the addition of water. Siena Sanded Grout GS300 is used for grouting tile joints 1/8" up to 1/2" wide in interior and exterior applications of most tiles and stones. Siena Sanded Grout GS300 can be used on floors and walls in residential and commercial projects. Siena Sanded Grout GS300 is mildew resistant, efflorescence resistant, available in 36 premium colors, and complies with the requirements of ANSI A118.6. Siena Admix AX100 is specially formulated to be used in combination with Siena Grouts to increase water retention, impart greater flexibility, improve bond strength and surface appearance. NOTE: Do not use any non-Siena brand additives with Siena Grouts.

Coverage

See grout chart

Packaging

25 lb (11.35 kg) bags

Pallet Quantities

100 bags per pallet - 2,500 lbs (1,135 kg) net

SKU	COLOR
See Price List	All 36 Colors



SIENA NON-SANDED GROUT NS200

A polymer-enhanced premium grout manufactured with portland cement to produce a high quality grout that requires only the addition of water. Siena Non-Sanded Grout NS200 is used for grouting tile joints 1/16" up to 1/8" wide in interior and exterior applications of most tiles and stones. Siena Non-Sanded Grout NS200 can be used on floors and walls in residential and commercial projects. Siena Non-Sanded Grout NS200 is mildew resistant, efflorescence resistant, available in 36 premium colors, and complies with the requirements of ANSI A118.6. Siena Admix AX100 is specially formulated to be used in combination with Siena Grouts to increase water retention, impart greater flexibility, improve bond strength, and surface appearance. NOTE: Do not use any non-Siena brand additives with Siena Grouts.

Coverage

See grout chart

Packaging

5 lb (2.27 kg) or 10 lb (4.5 kg) bags

Case Quantities

4 per case. 5 lb - 20 lbs (9 kg) net 4 per case. 10 lb- 40 lbs (18.1 kg) net

SKU COLOR See Price ListAll 36 Colors



1 GAL. KIT CONTENTS:
PART A - 1 Quart of Epoxy Resin (2 lbs.)
PART B - 1 Pint of Hardener/color (1 lb.)
PART C - Silica (10 lbs.)

SIENA EPOXY GROUT & MORTAR

A 100% solid epoxy that can be used as a grout or a mortar. Siena Epoxy Grout & Mortar can be used for setting and grouting tiles and stones, glass and metals, pavers, marbles and more over a variety of substrates. Siena Epoxy Grout & Mortar produces a high strength mortar and grout that is impermeable, stain and shock resistant. It has exceptionally high chemical resistance to many acids, alkalis, solvents and stains, making it ideal for usage in areas such as commercial kitchens, hospitals, countertops, floors and walls, interior and exterior, residential and commercial applications, and any area where the use of strong chemicals cause erosion and damage to traditional cementitious mortars beds and grout joints. Siena Epoxy Grout & Mortar conforms to the requirements for chemical-resistant, water cleanable, tile setting and grouting epoxy found in ANSI A118.3 and ANSI A108.6.

Coverage

See grout chart

Packaging

1/2 gal. (1.89 L) pail, 1 gal. (3.78 L) pail, 2 gal. (7.56 L) pail

Pallet Quantities

48 - 1/2 gal. pails per pallet, 792 lbs (359 kg) net 32 - 1 gal. pails per pallet, 1,056 lbs (478 kg) net 32 - 2 gal. pails per pallet, 2,112 lbs (956 kg) net

SKU	SIZE
See Price List	 /2 gal.
See Price List	 . 1 gal.
See Price List	 .2 gal.

CAULKS • STAINS



SIENA CAULK CX300 - SANDED OR SMOOTH

A siliconized acrylic latex caulk formulated for ease of use, durability and resists mold and mildew. Siena Caulk CX300 is flexible, long lasting and gives a water tight seal that resists cracking on most materials such as tile, stone, wood, porcelain, glass and metal. Siena Caulk CX300 can be used to seal around sinks, tubs, showers, countertops, baseboards, windows and door frames. Siena Caulk CX300 is an exceptional adhesive for tile, glass, wood, metal, and is ideal for setting marble vanity tops to their bases.

It is available in both sanded and smooth textures and in all of Siena's 36 premium colors.

Coverage

Approximately 25 linear feet (7.62 m) per cartridge for a 1/4" x 1/4" (6 x 6 mm) joint. Maximum joint width and depth should not exceed 1/4" (6 mm).

Packaging

10.5 fl.oz. (310 ml) bottle.

Case & Pallet Quantities

10 per case, 500 per pallet

SKU		COLOR
See Price List	All	36 Colors



SIENA GROUT STAIN ST300

A long lasting, waterborne urethane acrylic used to change and renew the color of sanded or non-sanded grout joints. It also seals and protects grout from moisture and staining. Siena Grout Stain ST300 is available in all of Siena's 36 premium grout colors. Siena Grout Stain ST300 can be used to change and renew the color of sanded and non-sanded grout joints from dark to light colors, or light to dark colors.

Coverage — Coverage May Vary. Per 8 fl. oz. (240 ml) 4" x 4" tile x 1/4" joint - 80 ft² 6" x 6" tile x 1/4" joint - 90 ft² 12" x 12" tile x 1/4" joint - 125 ft²

Packaging

8 fl.oz. (240 ml) bottle. **Case & Pallet Quantities** 12 per case, 480 per pallet

SKU COLOR See Price ListAll 36 Colors



Siena

GROUT COLOR SELECTION KIT

- All 36 Siena Grout Colors in one place
- Easy to use 1/4" wide plastic grout strips
- Convenient plastic case for years of protection
- Textured finish for accurate grout color samples
- Great in-store counter display stand alone
- Order one for all your tile and stone contractors

ASK YOUR SALESPERSON FOR YOURS TODAY







TYPE S • STONE VENEER MORTARS

SIENA TYPE S MORTAR

A mixture of portland cement, lime, and sand to produce a high quality non-modified bonding and grouting mortar that has good workability, sag resistance, flexural and compressive strength. Ideal for use in bonding and grouting most lightweight natural and manufactured stone veneers, thin brick, precast, masonry brick and block to solid surfaces such as concrete, stucco brown coat and masonry in residential and commercial, interior and exterior projects. Siena Type S Mortar is available in grey, tan and 15 standard and custom colors. Siena Admix AX300 can be used with Siena Type S Mortar to create a polymer-modified mortar for use on heavy stone installs or wherever polymer-modified mortars are required. Siena Type S Mortar exceeds ASTM C270.

Coverage - Coverage May Vary. Average install - 20 to 25ft² (6 to 7.6m²) **Packaging**

94 lb (43 kg) bags

Pallet Quantities

35 bags per pallet - 3,290 lbs (1,505 kg) net

SKU	COLOR
X130-3004	Grey
X130-2913	Tan
X130-2856	All Colors



SIENA STONE VENEER MORTAR (SVM)

A premium mixture of portland cement, lime, and sand to produce a high quality non-modified bonding and grouting mortar that has excellent workability, sag resistance, greater open time, flexural strength and compressive strength than basic Type S mortars. It has been specifically designed for the installation of most natural and manufactured stone veneers, precast, thin brick, masonry brick and block to solid surfaces such as concrete, stucco brown coat and masonry in residential and commercial, interior and exterior projects. Siena Stone Veneer Mortar (SVM) is available in grey, tan and 15 standard and custom colors. Siena Admix AX300 can be used with Siena Stone Veneer Mortar (SVM) to create a polymer-modified mortar for use on heavy stone installs or wherever polymer-modified Mortars are required. Siena Stone Veneer Mortar (SVM) exceeds ASTM C270.

Coverage - Coverage May Vary. Average install - 20 to 25ft² (6 to 7.6m²)


Packaging

94 lb (43 kg) bags

Pallet Quantities

35 bags per pallet - 3,290 lbs (1,505 kg) net

SKU	COLOR
X130-3006	Grey
X130-2914	Tan
X130-2858	All Colors



SIENA PREMIUM STONE VENEER MORTAR POLYMER-MODIFIED (PSVM)

A premium mixture of portland cement, lime, and sand to produce an exceptional polymer-modified bonding and grouting mortar that has excellent workability, sag resistance, greater open time and tensile strength, flexural strength and compressive strength than basic non-modified Type S mortars. It has been specifically designed for the installation of most natural and manufactured stone veneers, precast, thin brick, masonry brick and block to solid surfaces such as concrete, stucco brown coat and masonry in residential and commercial, interior and exterior projects. Siena Premium Stone Veneer Mortar (PSVM) is available in grey and 15 standard plus custom colors, and is used on heavy stone installs or wherever polymer-modified mortars are required. Siena Premium Stone Veneer Mortar (PSVM) exceeds ASTM C270 requirements.

Coverage - Coverage May Vary.

Average install - 20 to 25ft² (6 to 7.6m²)

Packaging

94 lb (43 kg) bags

Pallet Quantities

35 bags per pallet - 3,290 lbs (1,505 kg) net

SKU	co	DLOR
X130-3010		Grey
X130-3024	All C	olors



SIENA MASONRY & SURFACE SEALER

A high quality silane/siloxane-based sealer designed to seal a variety of porous substrates including masonry, natural and manufactured stone, brick, block, unglazed tile and stone, stucco, and other cementitious surfaces. Siena Masonry & Surface Sealer is UV stable and will not yellow or degrade over time. When properly applied, Siena Masonry & Surface Sealer will offer long lasting protection from the elements, water and oil based stains, is vapor permeability, dries clear, and retains the surface's natural appearance.

Coverage – *Coverage May Vary.* Approx: 100ft² to 200ft² (9.3m² to 18.6m²) per gal. **Packaging**

1 gallon (3.8 L) jugs - 4 per case 5 gallon (18.9 L) pails.

Pallet Quantities

128 – 1 gal. jugs per pallet, 1,075 lbs (487 kg) net 32 – 5 gal. pails per pallet, 1,344 lbs (609 kg) net

SKU	SIZE
X136-4018	 1 gal.
X136-4019	 . 5 gal.





VISIT OUR WEBSITE

SienaProducts.com

Access Siena's information on our full line of thin and medium set specialty mortars, waterproofing and antifracture membranes, self-leveling, deck muds and wall floats, stone veneer and Type S mortars, grouts, caulking sealers and admixtures.


KEY FEATURES:

- Complete, updated product catalogs
- Material Calculator
- Product Data and MSDS
- Technical data and bulletins
- Distributor locators
- Sample grout colors

LET US HELP YOU WITH YOUR NEXT EVENT!

- Special Siena Selling Events On-Site
- Hands-On Demonstrations Lunch & Learn
- Product Knowledge Classes Customers & Staff
- Special Promotions Raffles, Coupons, etc.
- Selling Tools Flyers, Posters, Product Samples
- In-Store Displays, Banners, and so much more . . .

For more info contact your local Siena Representative or Christine Camponovo at 800.600.6634 or CCamponovo@omega-products.com







DRAGONSKIN AND FRACTURE SHIELD SAMPLE CARDS ARE AVAILABLE

Order your free sample cards of DragonSkin and FractureShield complete with a product sample stapled to each card. This allows your customers to touch the product before purchasing; giving them the information they need to make a buying decision. Call or email to order your supply today.



TREAT YOUR CUSTOMERS TO THE BEST!

We have co-op opportunities available to co-brand your company name with the best name in tile and stone installation products . . . Siena. Our Siena line of fine apparel is made of top brand-name manufacturers for years of comfortable wear. Your customers will love the fit and feel of 100% cotton T-shirts; and our cotton-blend flex-fitted caps are top quality for long-lasting style. Also available, co-brand on our 5 gallon buckets for years of job site visibility and name recognition.

Call us today at 800.600.6634 or email us at Siena@omega-products.com





Siena Product installations are covered by a Ten (10), Fifteen (15), or Twenty-Five (25) Year System Warranty when select Siena and/or Omega products are used as detailed in charts below. Siena warranties Do Not supersede local codes, International Building Codes (IBC), International Residential Code (IRC), or building code officials. Check with local building codes prior to installation. Select items below for required System Warranty.

Properly prepared substrates include: Cured concrete (28 days), portland cement mortar beds, brown coat, backer boards (per manufacturer's specifications), gypsum boards (dry interior walls only), masonry block, brick, exterior grade plywood, well bonded existing tile and stone properly prepared with Siena Gripping Primer. Always check the Siena website for the most current product data sheets, technical bulletins, and acceptable practices at: SienaProducts.com

10 YEAR SYSTEM

15 YEAR SYSTEM

25 YEAR SYSTEM

SURFACE PREPARATION

(AS NEEDED)

Self-Level (SL20)

MEMBRANE

SP820 Floor Patch Gripping Primer

Self-Level (SLU)

Deck Mud

Wall Float

SURFACE PREPARATION		
	(AS NEEDED)	
	Self-Level (SLU)	
	Self-Level (SL20)	
	SP820 Floor Patch	
	Gripping Primer	
	Deck Mud	
	Wall Float	

	Gripping Primer	Gripping Primer	
	Deck Mud	Deck Mud	
	Wall Float		Wall Float
_			
	MEMBRANE		MEMBRANE
	MEMBRANE (AS NEEDED)		MEMBRANE (AS NEEDED)

SIENA MORTARS		
	M75 Fast Set Pro	
	M100 Multi Purpose	
	M200 Multi Plus Pro	
	M300 Pro Set Flex	
	M375 Glass Tile Pro	
	M225 LHT / LFT	
	M400 LHT / LFT Pro	
	EP200 Elasto Pro	
	Siena Crete + AX400	

Fracture Shield (Crack Isolation)

Sieria Crete + AA400
SIENA GROUTS
Sanded Grout
Non-Sanded Grout
Radiant Grout (RTU)
Brilliance Grout
Epoxy Grout

SURFACE PREPARATION		
(AS NEEDED)		
	Self-Level (SLU)	
	Self-Level (SL20)	
	SP820 Floor Patch	
	Gripping Primer	
	Deck Mud	
	Wall Float	

	Fracture Shield			
	(Crack Isolation)			
SIENA MORTARS				
	M200 Multi Plus Pro			
	M300 Pro Set Flex			
	M375 Glass Tile Pro			
	M225 LHT / LFT			
	M400 LHT / LFT Pro			

EP200 Elasto Pro

Siena Crete + AX400

		(AS NEEDED)
		Dragon Skin
		(Waterproofing)
		Fracture Shield
		(Crack Isolation)
		(Crack isolation)
		(Crack isolation)
3		SIENA MORTARS
ro		
ro		SIENA MORTARS

SIENA GROUTS			
	Sanded Grout		
	Non-Sanded Grout		
	Radiant Grout (RTU)		
	Brilliance Grout		
	Epoxy Grout		

SIENA GROUTS				
	Sanded Grout			
	Non-Sanded Grout			
	Radiant Grout (RTU)			
	Brilliance Grout			
	Epoxy Grout			

EP200 Elasto Pro

Siena Crete + AX400

Siena Crete + AX400

LIMITED WARRANTY

Siena Tile & Stone Installation Products [Siena], a division of Omega Products International [Omega], warrants that the products listed herein are free from manufacturing defects under normal usage and conditions for a period specified by the named system, from the date of purchase when installed in accordance with product specifications, the current TCNA (Tile Council of North America) guidelines, and approved installation practices on properly prepared substrates. It is the responsibility of the owner and/or contractor to obtain and understand Omega and Siena's current literature, specifications and appropriate published reports such as, but not limited to: the current TCNA handbook, current product data sheets, technical bulletins, etc. In order for this warranty to apply, the installation must be performed with one or more of the products listed herein, and based on the appropriate product(s) being installed on a properly prepared substrate. Omega is not responsible for workmanship that is not in accordance with the product specifications, product data sheet instructions, TCNA guidelines, and/or improperly prepared substrates. Structural movement, cracking, excessive deflection, lippage, warping, curling or defective tiles, improperly placed or lack of proper movement or control joints, flooding and/or water damage, acts of God, or any failures to the substrate, are not covered under this warranty. Shading and Efflorescence are inherent in all cement-based products and are not considered a manufactures defect. Omega will not be responsible for failures when the use of non-specified products, competitor, or any items or product is used to alter the original formulation of the Siena or Omega products that are not in accordance with specifications on the product's data sheet, and such uses and/or alterations will void this and all Omega and Siena warranties. This warranty is not transferable beyond the original owner.

REMEDY and EXCLUSIONS

It is expressly understood and agreed that the buyer's sole and exclusive remedy shall be that Omega will repair or replace, at their discretion, the affected area of the system. The cost to Omega shall not exceed the original square foot cost of the installation proven to be defective. Omega is not responsible for dye lots or shades of the finish materials. Under no circumstance shall Omega be liable for incidental or consequential damages. Omega makes no warranty of merchantability or fitness for a particular purpose with respect to the product sold herein. Handling and use of the products are beyond the control of Omega, therefore no warranty is made, expressed or implied, as to the results obtained from the use of the product. It is the responsibility of the buyer/installer to determine the suitability of the material for the intended use and purpose, and the buyer/installer assumes all risk regarding such suitability. This warranty takes the place of all other warranties, and there are no verbal agreements or other warranties, expressed or implied other than the warranty stated herein. This understanding shall not be modified except in writing by an officer of Omega Products International.

CLAIMS

Owner/Installer shall notify Omega immediately in writing within thirty (30) days of any alleged manufacturing defect in the material covered by this warranty. Owner/Installer will be required to provide proof of product purchase and use, and will provide Omega with reasonable time and opportunity to review and investigate the alleged manufacturing defect. For any claim presented under the warranty, Omega will provide the owner with a remedy as described above. For any claim that is not valid, Owner will pay Omega reasonable charges, including travel and labor associated with investigation of such claim. Address your claim to: Omega Products International, 1681 California Avenue, Corona, CA 92881

DEMAND THE HIGHEST QUALITY!

TAKING TILE & STONE INSTALLATION PRODUCTS FROM ORDINARY TO EXTRAORDINARY



SIENA HAS COMPLETE SYSTEM SOLUTIONS